

# **CUT SHEET**3900 DUBL-BOLT 2-Point Latching Flush Bolt



3900 DUBL-BOLT





### **ABOUT TRIMCO'S 3900 DUBL-BOLT**

Trimco's 3900 DUBL-BOLT is installed on the inactive leaf of a paired opening and operates a pair of flush bolts at the top and bottom of doors with one motion. The 3900 DUBL-BOLT is available for wood or hollow metal doors, with multiple strike options to pair with cylindrical and mortise locks. When ordering specify the type of door, strike, and lock type. Standard with 626 Satin Chrome Plated Finish.

### **FEATURES**

- 2-point latching flush bolt
- For wood doors & hollow metal doors
- Latches top and bottom with one lever
- Simple and easy to operate
- Standard for 1-3/4" thick door
- Americans with Disabilities Act Compliant

# URES APPLICATIONS

- Hospitality
- Multifamily & Mixed-Use
- Offices
- Government & Military

## How to specify your order:

			Door				U	
Family	Description	Ĺ	Height	Ī	Strike/Lock Type	Handing		Finish
3900 SEF	RIES		7.0 • 7'-0"		3 • #13 Mortise Lock, Center Auxillary Latch	R • Right Hand OR Left Hand Reverse	П	630 • Satin Stainless Steel
3900M	2-Point Latching		8.0 • 8'-0"		4 • #14 Mortise Lock, Lower Auxillary Latch	L • Left Hand OR Right Hand Reverse		
	Flush Bolt for inactive		8.6 • 8'-6"		5 • #5 Cylindrical/Tubular Lock		П	
		ľ	9.0 • 9'-0"	ľ	A • Include all Strikes (#13, #14 and #5)			
3900W	2-Point Latching		Or Specify				П	
	Flush Bolt for inactive		in Feet		*Standard with 1-3/4" Door Thickness			
							L	
Examples								
3900M-8	3.0-4L.630						П	
3900M		-	8.0	<u> </u> -	4	L	Ŀ	630
3900W-7.0-3R.630							П	
2000/4/			7.0	L	2	D	1	620