

DC050 DOOR CAP FOR USE WITH FLUSH BOLT OR CONCEALED VERTICAL ROD ORDER TEMPLATE

COMPANY INFORMATION				
COMPANY NAME:	CON	TACT NAME:		
ADDRESS:	EMA	IL ADDRESS:		
CITY: STATE/PF	ROVINCE: POS	TAL CODE:		DC050.630
PHONE: FAX:	DIST	RIBUTOR:		ISO VIEW OF INACTIVE DOOR SIDE
ADDITIONAL INFORMATION				
QUANTITY: FINISH:			CAP HEIGH	
MOUNTING: DOOR WIDTH: DOOR BEVEL: DOOR THICKNESS:				
HANDING: FB OR CVR MANUFACTURER:				
CUSTOMER NOTES:				DC050.630 ISO VIEW OF
NOTES.				ACTIVE DOOR SIDE
NOTES:	E	DOOR SIDE		B75 DISTANCE FROM DOOR FACE (SMALL SIDE) O CENTER OF CUT
-DIMENSIONS ARE IN INCHES -NUMBER OF SCREW HOLES VARY DEPENDING (-DO NOT PREDRILL DOOR -PRODUCT SHOWN IS FOR REFERENCE ONLY -PRODUCT COMES WITH #6 X 5/8 TRUSS HEAD -PRODUCT COMES WITH #8 TRUSS HEAD MACH -HORIZONTAL GRAIN DIRECTION FOR SATIN FI -TRIMCO ADDS 1/16" TO DIMENSIONS A AND B -PLACE ORDER WITH CUSTOMER SERVICE	Sheet metal screws for Si fine screws and sex bolts nishes for tolerance requireme	For Thru-Boi		FOR TRIMCO USE ONLY FOR TOP LEVEL ASSEMBLY, BOM, AND OTHER ENGINEERING DOCUMENTATION, SEE DWG# 19817 FOR INACTIVE VERSION 19819 FOR ACTIVE VERSION PART#:
-EMAIL: CSR@TRIMCOHARDWARE PHONE: (32 TEMPLATE# 22422	SHEET	1 4	OF 1	TRIANGLE BRASS MANUFACTURING
REVISION# 1	This template is provided for	use only on the	job for which it	1351 ROCKY POINT DRIVE
APPROVED ON: 5/3/2023	was requested. Trimco reserves the right to make design changes without notice. Trimco will not be responsible for errors or damage caused by the use of out-of-date templates. WWW.TRIMCOHARDW.			
	errors or damage caused by the use of out-of-date templates.			