

SUPPLIED WITH TWO 5/16-18 X 2.5 FLAT HEAD, PHILIPS DRIVE MACHINE SCREWS AND TWO 5/16 FINISH WASHERS.

EXCEPTION - 1191E-8-1/2 HAS 1/4-20 TAPPED HOLES AND IS SUPPLIED WITHOUT ANY HARDWARE.

TRIMCO	Α	B	С	D	E
PART #	MAT'L DIA	CEN. TO CEN.	CLEARANCE	OFFSET	RADIUS
1191E-1	.75	8.00	2.50	3.88	.75
1191E-2	.75	10.00	2.50	3.88	.75
1191E-3	1.00	10.00	2.50	4.38	1.00
1191E-4	1.00	12.00	2.50	4.38	1.00
1191E-5	1.00	18.00	2.50	4.38	1.00
1191E-4J	1.25	12.00	2.88	5.25	1.25
1191E-5J	1.25	18.00	2.88	5.25	1.25
1191E-8-1/2	1.00	8.50	1.88	4.00	1.00

 NOTE: This template is provided for use only on the job for which is was requested.
 DATE

 Trimco reserves the right to make design changes without notice. Trimco will
 0

 not be responsible for errors or damage caused by the use of out-of-date templates.
 3/23/06